




REVISIONS				
REV.	DESCRIPTION OF CHANGE	DATE	BY	APPROVED
0	INITIAL LAIRD RELEASE	6/28/2021	FJG	FJG

- NOTES:
1. CRITICAL DIMENSIONS ARE DESIGNATED BY 
  2. REFERENCE DIMENSIONS WILL BE SHOWN IN PARENTHESES (DIM)
  3. FABRIC SEAM LOCATION MAY VARY
  4. FOAM: POLYURETHANE
  5. FABRIC: NICKEL PET-TAF FR EcoGreen
  6. TAPE: 3.18mm WIDE HI-TEMP ADHESIVE
  7. LINER: NO EXTENDED RELEASE LINER
  8. CARRIER: NO CARRIER

- ROHS -												4. FOAM: POLYURETHANE	
THIS PRODUCT IS FULLY COMPLIANT TO LT-GES-001 WHICH MEETS OR EXCEEDS COMPLIANCE REQUIREMENTS OF EUROPEAN DIRECTIVE 2011/65/EU 'RESTRICTION OF USE OF HAZARDOUS SUBSTANCES'												5. FABRIC: NICKEL PET-TAF FR EcoGreen	
												6. TAPE: 3.18mm WIDE HI-TEMP ADHESIVE	
												7. LINER: NO EXTENDED RELEASE LINER	
												8. CARRIER: NO CARRIER	
*CAD MAINTAINED DRAWING* REV. CONTROLLED DOCUMENT MANUAL CHANGES UNAUTHORIZED PRINTED COPIES OF THIS DOCUMENT ARE CONSIDERED UNCONTROLLED.	BLOCK TOLERANCES APPLY TO METRIC UNITS ONLY. DUAL DIMENSIONS IF SHOWN ARE FOR REFERENCE ONLY AND ARE DISPLAYED IN 3 PLACES FOR CONVERSION PURPOSES ONLY	UNITS: MM [INCH]			MATERIAL:	PART DESCRIPTION:		LAIRD PART NUMBER :  4295PAX1R					
		TOLERANCES: X.XX = ± 0.5			X1R (SEE NOTES)		SHIELDING GASKET						
		LENGTHS: 1 - 152 = ± 0.8 152 - 279 = ± 1.3 279 - 1219 = ± 2.5 1219 - 1778 = ± 4.8 1778 - 2438 = ± 6.4	3RD ANGLE PROJECTION 		THICKNESS:	CUSTOMER:		PROGRAM NAME:	MODEL BY:	DATE:	REV:  0		
		ANGULAR: X.X° = ± 1.0°	DESIGNED IN SOLIDWORKS		SEE DRAWING		N/A		N/A			FRANK GIBILTERRA	6/28/2021
3D MODEL REQUIRED FOR COMPLETE DOCUMENTATION	INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND PROPRIETARY TO LAIRD. IT MAY NOT BE DISCLOSED TO ANYONE WITHOUT WRITTEN AUTHORIZATION FROM LAIRD TECHNOLOGIES.	SCALE: 15:1	SHEET 1 OF 1		SIZE  B	FINISH:  N/A		CUSTOMER PART NUMBER :  N/A		APPROVED BY:  FRANK GIBILTERRA		DATE:  6/28/2021	
								LAIRD PART FAMILY/GROUP:  FABRIC OVER FOAM		LAIRD STD PART REF:  N/A			