



REVISIONS				
REV.	DESCRIPTION OF CHANGE	DATE	BY	APPROVED
0	INITIAL LAIRD RELEASE	6/28/2021	FJG	FJG

- NOTES:
1. CRITICAL DIMENSIONS ARE DESIGNATED BY
 2. REFERENCE DIMENSIONS WILL BE SHOWN IN PARENTHESES (DIM)
 3. FABRIC SEAM LOCATION MAY VARY
 4. FOAM: POLYURETHANE
 5. FABRIC: NICKEL PET-TAF FR EcoGreen
 6. TAPE: 1.27mm WIDE HI-TEMP ADHESIVE
 7. LINER: NO EXTENDED RELEASE LINER
 8. CARRIER: NO CARRIER

<div>- ROHS -</div>												4. FOAM: POLYURETHANE	
THIS PRODUCT IS FULLY COMPLIANT TO LT-GES-001 WHICH MEETS OR EXCEEDS COMPLIANCE REQUIREMENTS OF EUROPEAN DIRECTIVE 2011/65/EU 'RESTRICTION OF USE OF HAZARDOUS SUBSTANCES'												5. FABRIC: NICKEL PET-TAF FR EcoGreen	
												6. TAPE: 1.27mm WIDE HI-TEMP ADHESIVE	
												7. LINER: NO EXTENDED RELEASE LINER	
												8. CARRIER: NO CARRIER	
CAD MAINTAINED DRAWING REV. CONTROLLED DOCUMENT MANUAL CHANGES UNAUTHORIZED PRINTED COPIES OF THIS DOCUMENT ARE CONSIDERED UNCONTROLLED.	BLOCK TOLERANCES APPLY TO METRIC UNITS ONLY. DUAL DIMENSIONS IF SHOWN ARE FOR REFERENCE ONLY AND ARE DISPLAYED IN 3 PLACES FOR CONVERSION PURPOSES ONLY	UNITS: MM [INCH]			MATERIAL:	PART DESCRIPTION:		LAIRD PART NUMBER : 4520PAX1R					
		TOLERANCES: X.XX = ± 0.5			X1R (SEE NOTES)	SHIELDING GASKET							
		LENGTHS: 1 - 152 = ± 0.8 152 - 279 = ± 1.3 279 - 1219 = ± 2.5 1219 - 1778 = ± 4.8 1778 - 2438 = ± 6.4	3RD ANGLE PROJECTION 	THICKNESS:	CUSTOMER:		PROGRAM NAME:	MODEL BY:	DATE:	REV: 0			
		ANGULAR: X.X° = ± 1.0°	DESIGNED IN SOLIDWORKS	SEE DRAWING	N/A		N/A	FRANK GIBILTERRA	6/28/2021				
3D MODEL REQUIRED FOR COMPLETE DOCUMENTATION	INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND PROPRIETARY TO LAIRD. IT MAY NOT BE DISCLOSED TO ANYONE WITHOUT WRITTEN AUTHORIZATION FROM LAIRD TECHNOLOGIES.	SCALE: 30:1	SHEET 1 OF 1	SIZE B	N/A	CUSTOMER PART NUMBER :	APPROVED BY:	DATE:					
						LAIRD PART FAMILY/GROUP:		LAIRD STD PART REF:					
						FABRIC OVER FOAM		N/A					