



CORE DIMENSIONS 66T0190-80P

UNCOATED CORE		MM	INCHES	MM	INCHES
OD	4.83	(.190)	±	.15	(.006)
ID	2.29	(.090)	±	.15	(.006)
TH	2.97	(.117)	±	.15	(.006)
SINGLE PARAYLENE		MM	INCHES	MM	INCHES
OD	4.85	(.191)	±	.15	(.006)
ID	2.26	(.089)	±	.15	(.006)
TH	3.00	(.118)	±	.15	(.006)

WEIGHT / K 0.20226 .4459 LBS
 INITIAL PERMEABILITY **3200**

ELECTRICAL SPECIFICATION									
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	URNS
L1 Ref.	-25.0%	1.07	1.420	1.78	25.0%	100	1.60	10	1

COATING SPECIFICATIONS			
TYPE	Ref. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Paraylene	(0.0127 / 0.5)	1000	.22

NOTES: 1. DC BIAS REQUIREMENT:
 100 kHz / 383.8 mV / 24 turns / 38 AWG

H(Oe)	0.71
DC Bias (mA)	24.0
Min. Inductance (uH): (0 °C to 70 °C)	350.0

2. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	Original Draft	2011/6/21	Jcai

Date: 2011-6-21	DWG # 66T0190-80P-A	Rev:
Drawn By: Jcai	Title # 66T0190-80P	A

Steward This document contains information which is proprietary to Steward. No production or publication of tis document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT - FOR REFERENCE ONLY