



“CARRIER CLASS” POWER OVER ETHERNET SYSTEM

The POE-55i4sG-AFI is an advanced 802.3af compliant power supply/inserter. The power supply is autoranging on the input and has a regulated voltage output and it has overload and short circuit protection. The POE-55i4sG-AFI is not a proprietary unit. It will function with any equipment which is compliant with the IEEE 802.3af POE standards. The POE-55i4sG-AFI does not include the intelligent detection algorithms detailed in the 802.3af spec which means that the POE-55i4sG-AFI will power up any device connected to it. The power is supplied on ethernet pins 4/5 (V+) and 7/8 (V-). The POE-55i4sG-AFI comes complete with a standard North American 115VAC power cord. International cords are available upon request.

Using power over Ethernet to power remote devices has several advantages including;

- The power supply can be centrally located where it can be attached to an uninterruptible power supply.
- The user has the ability to easily power on and reset the attached equipment from a remote location.
- There is no need to run additional power cabling to the device as power can be supplied over the CAT5 ethernet cable.
- The power supply can power a remote device up to 300 feet away, limited only by the Ethernet standard.

FEATURES

- “Carrier class” power over ethernet system
- Auto ranging power supply/ inserter
- Built-in ethernet surge protection to prevent equipment damage
- Overload and short circuit protection
- Minimum cross talk and insertion loss
- Advanced switching technology – runs cool
- Powers clients which accept power on unused ethernet pins 4,5,7,8
- FCC and CE approved
- Current indicator (CI) option available

MARKETS

- Remote routers, access points, and bridges
- Remote networking equipment
- Remote camera systems
- 400MHz to 10GHz systems
- SOHO equipment
- IP phone systems

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

SPECIFICATIONS

Input Voltage:	90 – 264VAC @ 47 – 63Hz
Input Current:	0.85A @ 120VAC 0.93A @ 230VAC
Efficiency:	78% min at Full Load, 120Vac and 230Vac Input Voltage
Output Voltage:	+55V
Maximum Load:	0.55A Min
Power	30W
Minimum Load:	0.01A Min
Output Noise:	1%
Output Ripple:	1%
Line Regulation:	1%
Load Regulation:	5%
Short Circuit Protection:	Output short GND terminal will not damage the power supply and will auto-reset. Input has fuse protection.
Safety Standards:	Meets UL1950, CSA 22.2 and TUV EN60950
EMC:	Meets FCC Class B , NE55022 Class B
Over Current:	120% ~ 160% @120Vac Input F.L
Operating Temperature:	-25 to +65 deg C
Storage Temperature:	-40 to +80 deg C
Operating Humidity:	5% to 90%
Cooling:	Free air cooling
Size (L x W x H):	125 x 75 x 38mm

LED (Green): Include PWR-OK
 Note 1: Noise bandwidth is from DC to 20Mhz. Ripple & Noise is measured by Paralleling a 0.1uF metalize capacitor on the test point.

RJ-45 INPUT (DATA ONLY)			RJ-45 OUTPUT (DATA & POWER)	
-------------------------	--	--	-----------------------------	--

Pin	Symbol	Description	Symbol	Description
1	RX+	Data Receive	RX+	Data Receive
2	RX-	Data Receive	RX-	Data Receive
3	TX+	Data Transmit	TX+	Data Transmit
4	Data	Data	+Vdc	power(+)+Data
5	Data	Data	+Vdc	power(+)+Data
6	TX-	Data Transmit	TX-	Data Transmit
7	Data	Data	-Vdc	power(-)+Data
8	Data	Data	-Vdc	power(-)+Data

Note : 1. DC output gnd and Vin+/- should not be shorted to ground(FG).



Power Supply Inserter AC Power IN (90-264VAC)@120V/230



Power Supply Inserter Data IN

Power Supply Inserter Data/POE OUT