



# TYS30156R8M-10

## PHYSICAL DIMENSIONS:


A	3.00	±	0.20
B	3.00	±	0.20
C	1.50	+ / -	0.20 / 0.30
D	1.10	±	0.30
E	0.80	±	0.30



## RECOMMENDED SOLDERING CONDITIONS




## LAND PATTERNS FOR REFLOW SOLDERING



## ELECTRICAL SPECIFICATION


	Min	Nom	Max
INDUCTANCE (uH) L @ 100 KHz/1V ±20%	5.44	6.80	8.16
DCR (Ω)		0.200	0.260

## CHARACTERISTICS OF TEMPERATURE RISE



Saturation Current(A)	0.85	Max.
SRF (MHz)	39	Ref.
Temperature Rise Current (A)	0.85	Max.

## CURRENT VS INDUCTANCE DROP IN RATES



## NOTES:

- OPERATION TEMPERATURE RANGE: -40°C~+125°C (INCLUDING SELF-HEATING).
- STORAGE TEMPERATURE RANGE (PACKAGING CONDITIONS): -10°C TO +40°C AND RH 70% (MAX.)
- UNLESS OTHERWISE SPECIFIED, THE STANDARD ATMOSPHERIC CONDITIONS FOR MEASUREMENT/TEST AS:  
A. AMBIENT TEMPERATURE: 20±15°C.  
B. RELATIVE HUMIDITY: 65%±20%.
- SATURATION CURRENT IS THE DC CURRENT AT WHICH THE INDUCTANCE DROPS OFF APPROXIMATELY 30% FROM ITS VALUE WITHOUT CURRENT.(AMBIENT TEMPERATURE 25±5°C)
- TEMPERATURE RISE CURRENT (IRMS):  
DC CURRENT THAT CAUSES THE TEMPERATURE RISE ( $\Delta T \leq 40^\circ C$ ) FROM 25°C AMBIENT.

DIMENSIONS ARE IN mm .				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
E	CHANGE DIMENSIONS:C/D/E	07/28/16	QIU				
D	CHANGE DIMENSIONS AND SPE	05/04/16	QIU				
C	MODIFY "C"	04/21/16	QIU				
B	CHANGE LOGO	07/28/15	QIU				
A	ORIGINAL DRAFT	08/07/12	QIU				
PROJECT/PART NUMBER: TYS30156R8M-10				REV	E	PART TYPE: POWER INDUCTOR	DRAWN BY: QIU
DATE: 08/07/12				SCALE:	NTS	SHEET:	
CAD #				TOOL #	-	1 of 1	
REV	DESCRIPTION	DATE	INT	TYS30156R8M-10-E			