




CORE DIMENSIONS				28T0201-100	
UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	5.10	(.201)	±	.15	(.006)
ID	1.45	(.057)	±	.15	(.006)
TH	3.40	(.134)	±	.15	(.006)

WEIGHT / K 0.3113 KGS .6862 LBS

INITIAL PERMEABILITY 850

ROOM TEMPERATURE ELECTRICAL SPECIFICATION								
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	TURNS
L1-1T(REF.)	-25.0%	0.55	0.727	0.91	25.0%	100	2.42	1
NET IMPEDANCE	MIN (Ω)	MIN TOL.	NOM (Ω)			FREQ. (MHz)		TURNS
Z1 (REF.)	-	-	36	-	-	25		1
Z2	41	(-25%)	55	-	-	100		1

NOTES:

1. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	New release	2020/4/19	WS

Date: 2020/4/19	Tooling: T0201	Rev:
Drawn By: WS	Title # 28T0201-100	A
Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.		