


**CORE DIMENSIONS****28T0375-100****UNCOATED CORE**

	MM	INCHES		MM	INCHES
OD	9.53	(.375)	±	.25	(.010)
ID	4.75	(.187)	±	.25	(.010)
TH	3.18	(.125)	±	.13	(.005)

EPOXY COATING**28T0375-10H**

OD	9.68	(.381)	±	.41	(.016)
ID	4.60	(.181)	±	.41	(.016)
TH	3.33	(.131)	±	.28	(.011)

WEIGHT / K

0.8312 KGS

1.8324 LBS

INITIAL PERMEABILITY

850**ROOM TEMPERATURE ELECTRICAL SPECIFICATION**

	MIN. TOL.	MIN. (μ H)	NOM. (μ H)	MAX. (μ H)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	TURNS
L	-20.0%	0.30	0.376	0.45	20.0%	100	3.24	10	1
Q		REF				100	3.24	10	1
Net impedance		TOL.	MIN. (Ω)	NOM. (Ω)		FREQ. (kHz)			TURNS
Z1 (REF.)	-25.0%		11.87	15.82		25			1
Z2	-25.0%		22.42	29.89		150			1

COATING SPECIFICATIONS

	TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
	Epoxy	(0.1524 / 6.0)	1000	.83

NOTES:



Rev	Description	Date	INT
A	Original Draft	2008-6-24	Jcai

Date: 2008-6-24	DWG # 28T0375-10H-A	Rev:
Drawn By: Jcai	Title # 28T0375-10H	A

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT