




CORE DIMENSIONS				28T0562-300	
UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	14.27	(.562)	±	.25	(.010)
ID	6.35	(.250)	±	.25	(.010)
TH	5.30	(.209)	±	.20	(.008)

WEIGHT / K 3.3140 KGS 7.3061 LBS
INITIAL PERMEABILITY 850

ROOM TEMPERATURE ELECTRICAL SPECIFICATION								
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	TURNS
L1-1T(REF)	-25.0%	0.55	0.73	0.91	25.0%	100	8.83	1
NET IMPEDANCE	MIN (Ω)	MIN TOL.	NOM (Ω)			FREQ. (MHz)		TURNS
Z1 (REF.)	-	-	36	-	-	25		1
Z2	41	(-25%)	55	-	-	100		1

NOTES:

1. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	New release	2020/4/20	WS

Date: 2020/4/20	Tooling: B0562	Rev: A
Drawn By: WS	Title # 28T0562-300	

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.