

Tflex™ B200 Series

Thermal Gap Filler



PRODUCT DESCRIPTION

Tflex B200 is a reliable, compliant thermal interface material offering good thermal performance and easier handling and features a range of multiple surface and enforcement options for a variety of applications. This gap filler's low modulus interface and softness relieves mechanical stress and reduces thermal resistance.

Tflex B200 helps absorb shock, resulting in improved device reliability over the long term. It has high dielectric insulation which works to protect against dielectric breakdown in or between devices. Tflex B200 as a standard product is naturally tacky on both sides and requires no additional adhesive coating to inhibit thermal performance.

Tflex B200MFG, an option featuring fiberglass in the middle, has strong tensile and both sides exhibit tackiness properties. This helps prevent deforming during manual or automated assembly.

Tflex B200FG, has fiberglass enforcement located near one side. It offers a higher deflection than the B200MFG option, and provides protection close to one side.

FEATURES AND BENEFITS


- Thermal Conductivity of 2W/m.K
- Compliant to application surfaces, long term reliability
- Shock resistance in automotive applications
- Fiberglass enforcement, protection against breakthrough or deforming
- Protection with high DBV


TYPICAL PROPERTIES

PROPERTIES	TYPICAL VALUE	TEST METHOD
Construction & Composition	Ceramic filled silicone sheet	N/A
Color	Grey	Visual
Thickness Range	1mm – 5mm	N/A
Thermal Conductivity	2.0 W/mk	ASTM D5470
Density	2.2 g/cc	Helium Pycnometer
Thermal Resistance (1.0mm) @ 10 psi, 50 °C	1.10 Cin2/W	ASTM D5470
Temperature Range	-40°C to 150°C	Laird Test Method
Outgassing TML (%)	0.32	ASTM E595
Hardness Shore 00 (3 second)	42	ASTM D2240
Volume Resistivity (Ω cm)	2 x 10^13	ASTM D257
UL Flammability Rating	V-0	UL 94

Tflex™ B200 Series

Thermal Gap Filler





AVAILABILITY

- 1.00 mm (0.040") to 5.0 mm (0.200") thick material available in 0.25mm (0.010") increments
- Available in standard sheet sizes of 18" x 18", 9" x 9" or custom converted die cut parts
- MFG: Fiberglass layer added in the middle, FG: Fiberglass added to one side

PART NUMBER SYSTEM

TflexTM indicates Laird elastomeric thermal gap filler product line. B2xxx indicates TflexTM B200 product line with thickness in mils EXAMPLES: TflexTM B240 = 1000 microns / 0.040" thick material

THR-DS Tflex B200 05-26-21

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies? Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2021 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.