



CORE DIMENSIONS		28T0140-400			
UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	3.50	(.138)	±	.15	(.006)
ID	1.50	(.059)	±	.15	(.006)
TH	6.50	(.500)	±	.20	(.008)

WEIGHT / K 0.4863 KGS 1.0720 LBS  
 INITIAL PERMEABILITY 850

ROOM TEMPERATURE ELECTRICAL SPECIFICATION								
L1-REF	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	URNS
	-25.0%	0.70	0.936	1.17	25.0%	100	2.72	1
NET IMPEDANCE	MIN (Ω)	MIN TOL.	NOM (Ω)			FREQ. (MHz)		URNS
Z1 (REF.)	-	-	46	-	-	25		1
Z2	53	(-25%)	71	-	-	100		1

NOTES:

1. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	New release	2020/4/11	WS

Date: 2020/4/11	Tooling: B0141	Rev: A
Drawn By: WS	Title # 28T0140-400	

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.