



CORE DIMENSIONS 33T0190-100

UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	4.83	(.190)	±	.13	(.005)
ID	2.29	(.090)	±	.13	(.005)
TH	1.27	(.050)	±	.13	(.005)

SINGLE PARAYLENE 33T0190-10P					
	MM	INCHES		MM	INCHES
OD	4.85	(.191)	±	.13	(.005)
ID	2.26	(.089)	±	.13	(.005)
TH	1.30	(.051)	±	.13	(.005)

WEIGHT / K 0.0878 KGS .1937 LBS
 INITIAL PERMEABILITY 2700

ROOM TEMPERATURE ELECTRICAL SPECIFICATION								
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (V)	TURNS
L	-20.0%	0.410	0.512	0.615	20.0%	100	≤ .00034	1
Q		62				100	≤ .00034	1

COATING SPECIFICATIONS			
TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Paraylene	(0.0127 / 0.5)	1000	.22

NOTES:



Rev	Description	Date	INT
A	Original Draft	1998-2-24	TPM
B	Reactive and removed the "Q" & "D" coating	2007-9-17	Wxu

Date: 2007-9-17	DWG # 33T0190-10P-B	Rev:
Drawn By: Wxu	Title # 33T0190-10P	B

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT