



NET IMPEDANCE (Z)						
Frequency	0.5 MHz	1 MHz	5 MHz	10 MHz	25 MHz	
Nominal (REF)	53 Ω	60 Ω	48 Ω	39 Ω	35 Ω	
Minimum	40 Ω	45 Ω	36 Ω	29 Ω	26 Ω	

FERRITE CORE DIMENSIONS (SPEC): mm [in]

A	32.00 [1.260]	±	0.60 [.024]
B	18.20 [.717]	±	0.40 [.016]
C	38.00 [1.496]	±	0.60 [.024]
D	8.00 [.315]	±	0.20 [.008]
E	4.00 [.157]	±	0.25 [.010]

WEIGHT/1000 33.30 kgs [73.40 Lbs]

NOTES: UNLESS OTHERWISE SPECIFIED

1. COSMETIC SPECIFICATION REFER TO WI-QA-038.
2. THE CONTACT SURFACE NEED TO BE POLISHED.



DIMENSIONS ARE IN mm[INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
PROJECT/PART NUMBER:				REV	PART TYPE:	DRAWN BY:	
35U1260-320				B	CNZ CORE	QIU	
B	CHANGE IMPEDANCE	04/09/18	QIU	DATE:	04/08/18	SCALE:	1 : 1
A	NEW RELEASE	04/08/18	QIU	CAD #	35U1260-320-B	TOOL #	U1260
REV	DESCRIPTION	DATE	INT	MATERIAL: Ferrite			