



CORE DIMENSIONS **40T0135-100**

UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	3.43	(.135)	±	.13	(.005)
ID	1.78	(.070)	±	.13	(.005)
TH	2.06	(.081)	±	.13	(.005)

SINGLE PARAYLENE					
	MM	INCHES		MM	INCHES
OD	3.45	(.136)	±	.13	(.005)
ID	1.75	(.069)	±	.13	(.005)
TH	2.08	(.082)	±	.13	(.005)

WEIGHT / K 0.0677 KGS .1493 LBS
 INITIAL PERMEABILITY **10000**

ROOM TEMPERATURE ELECTRICAL SPECIFICATION									
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	URNS
L1-1T	-30.0%	1.892	2.703	3.513	30.0%	100	0.73	10	1
Q		REF 4				100	0.73	10	1

COATING SPECIFICATIONS			
TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Paraylene	(0.0127 / 0.5)	1000	.10

NOTES:



Rev	Description	Date	INT
G	Re-active print	2013-8-2	Jcai

Date: 2013-8-2	DWG # 40T0135-10P-G	Rev:
Drawn By: Jcai	Title # 40T0135-10P	G

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT