



CORE DIMENSIONS					40T0632-000	
UNCOATED CORE						
	MM	INCHES		MM	INCHES	
OD	16.00	(.630)	±	.58	(.023)	
ID	9.00	(.354)	±	.58	(.023)	
TH	5.00	(.197)	±	.13	(.005)	
EPOXY COATING					40T0632-00H	
OD	16.15	(.636)	±	.74	(.029)	
ID	8.85	(.348)	±	.74	(.029)	
TH	5.15	(.203)	±	.28	(.011)	

WEIGHT / K 3.3502 KGS 7.3859 LBS
 INITIAL PERMEABILITY 10000

ROOM TEMPERATURE ELECTRICAL SPECIFICATION									
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	TURNS
L1-1T	-30.0%	4.03	5.75	7.48	30.0%	100	7.56	10	1
L2-10T	-30.0%	402.8	575.4	748.0	30.0%	100	75.60	10	10
Q		4							

COATING SPECIFICATIONS			
TYPE	Ref. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Epoxy	(0.1524 / 6.0)	1000	2.13

NOTES:

1. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	Original Draft Brochure 58 rev2 12/2004	1/24/2005	TPM
B	Revised Template	5/22/2006	WMM
C	Update logo and notes	6/12/2020	WS

Date: 5/22/2006	DWG # 40T0632-00H-C	Rev: C
Drawn By: WMM	Title # 40T0632-00H	

Laird This document contains information which is proprietary to laird. No production or publication of this document in whole or in part shall be made without written authorization from Laird.