
IC0805B222R-10

PHYSICAL DIMENSIONS:




NOTES: UNLESS OTHERWISE SPECIFIED

- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 4000 PCS/REEL, EMBOSSED PLASTIC TAPE.
- 2. TERMINATION FINISH IS 100% MATTE Sn OVER Ni.
- COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. I (MAX.) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MAXIMUM TEMPERATURE RISE OF 40°C OVER AMBIENT.
- 5. OPERATING TEMP. RANGE: -40°C~+125°C. (INCLUDING SELF-HEATING)

ELECTRICAL CHARACTERISTICS:


	2.420	Max				
	2,420	Max				
L (nH) ± 10%	2,200	Nom				
	1,980	Min				
Q (Min)	45 10 50 0.65					
Freq. (MHz)						
Self-Resonant Freq (MHz)						
DCR(Max) Ω						
l (Max)	20	200mA				

LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.763 [.030] to this dimension.)

RECOMMENDED SOLDERING CONDITIONS





		DIMENSIONS ARE IN mm [INCHE	:S].		This print is the property of Laird					
-	F	REMOVE NOTE 5	07/21/16	QIU	Tech, and is loaned in confident subject to return upon request			_	= _4	٦,
	E	ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE	08/05/13	QU	with the understanding that no copies shall be made without the written consent of Laird Tech.	ne	Laird			
	D	UPDATE COMPANY LOGO	06/23/08	JRK	rights to design or invention are		_			
	C	MODIFY NOTES CHANGE C&D DIMS &	01/17/07	JRK	reserved. PROJECT/PART NUMBER:	- 1-	<u> </u>	I		T==
	SEL	SELF-RESONANT FREQUENCY			· ·	- 1 **	EV	PART TY		DRAWN BY:
	В	B CHG P/N ADD 30mA TO ELECT BOX REV LANDPATTERN DIMS REVISE/ADD NOTES	02/02/06	JRK	IC0805B222R-10		F	CO-	-FIRE	JRK
						SCALE	i N	TS	SHEET:	-
-	Α	ORIGINAL DRAFT	05/13/04	JRK	, ,	TOOL			4	
	REV	DESCRIPTION	DATE	INT					1	of 1